

# **Submittal Data Sheet**

Project Name:	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:

# **Performance**

Indoor Unit Model No:	FXDQ12MVJU
Rated Cooling Capacity (Btu/hr):	12000
Sensible Capacity (Btu/hr):	8800
Cooling Input Power (kW):	0.095
Rated Heating Capacity (Btu/hr):	13500
Heating Input Power (kW):	0.076

Indoor Unit Type: [	ouct Mo	ounted Slim Type (Low Static)
Rated Cooling Conditions		Indoor: 80°F DB/67°F WB
		Ambient: 95°F DB/75°F WB
Rated Heating Conditions		Indoor: 70°F DB/60°F WB
		Ambient: 47°F DB/43°F WB
Rated Piping Length (	ft)	25
Rated Height Separati	ion (ft)	0

## **Indoor Unit Details**

Power Supply (V/Hz/Ph:)	208-230/60/1ph
Power Supply Connections:	L1, L2, Ground
Min. Circuit Amps MCA (A):	0.9
Max. Overcurrent Protection (MC	<i>P) (A):</i> 15
Dimensions (HxWxD):	7-7/8x27-9/16x24-7/16
Panel (HxWxD):	N/A
Net Weight (lbs):	51
Net Weight with Panel (lbs):	

Airflow Rate (CFM wet coil)	280//226
Moisture Removal (pt/h):	
Gas Pipe Connection (inch):	1/2
Liquid Pipe Connection (inch):	1/4
Condensate Connection (inch):	1-1/32
Sound Pressure Level (dBA):	33
Sound Power Level (dBA):	50.8 c/h
External Static Pressure/Max (inWg):	0.04 / 0.12
Controller Name:	

# FXDQ12MVJU

# FXDQ12MVJU

Std U.S. Warranty: 7yrs Compressor, 1yrs Parts



# **Submittal Data Sheet**

Project Name:	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:

### **Dimensional Drawing - Indoor Unit**

FXDQ12MVJU

