

Submittal Data Sheet

Project Name:
Location:
Engineer:
Submitted to:
Submitted by:
Reference:

Approval:
Date:
Construction:
Unit #:
Drawing #:

Performance

Indoor Unit Model No:	FXFQ12PVJU
Rated Cooling Capacity (Btu/hr):	12000
Sensible Capacity (Btu/hr):	10300
Cooling Input Power (kW):	0.034
Rated Heating Capacity (Btu/hr):	13500
Heating Input Power (kW):	0.03

Indoor Unit Type:	Round Flow Cassette
Rated Cooling Conditions	Indoor: 80°F DB/67°F WB
	Ambient: 95°F DB
Rated Heating Conditions	Indoor: 70°F DB
	Ambient: 47°F DB/43°F WB
Rated Piping Length (ft)	25
Rated Height Separation (ft)	0

Indoor Unit Details

208-230/60/1ph
L1, L2, Ground
0.3
<i>IOP) (A):</i> 15
9-11/16x33-1/16x33-1/16
2x37-3/8x37-3/8
43
55.2

Airflow Rate (CFM wet coil)	460/390/350
Moisture Removal (pt/h):	
Gas Pipe Connection (inch):	1/2
Liquid Pipe Connection (inch):	1/4
Condensate Connection (inch):	1-1/4
Sound Pressure Level (dBA):	30
Sound Power Level (dBA):	
External Static Pressure/Max (inWg):	0 / 0
Controller Name:	



FXFQ12PVJU

Std U.S. Warranty: 7yrs Compressor, 1yrs Parts

Daikin AC (Americas), Inc., 1645 Wallace Drive - Suite 110, Carrollton, TX 75006

Daikin AC TRL Generated Submittal Data

enerated Submittal Data (Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)



Submittal Data Sheet

Project Name:		
Location:	Approval:	
Engineer:	Date:	
Submitted to:	Construction:	
Submitted by:	Unit #:	
Reference:	Drawing #:	

Dimensional Drawing - Indoor Unit

Daikin AC TRL Generated Submittal Data

FXFQ12PVJU

