

Project Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted to: \_\_\_\_\_  
 Submitted by: \_\_\_\_\_  
 Reference: \_\_\_\_\_

Approval: \_\_\_\_\_  
 Date: \_\_\_\_\_  
 Construction: \_\_\_\_\_  
 Unit #: \_\_\_\_\_  
 Drawing #: \_\_\_\_\_

**Performance**

Indoor Unit Model No:	FXFQ24PVJU
Rated Cooling Capacity (Btu/hr):	24000
Sensible Capacity (Btu/hr):	18900
Cooling Input Power (kW):	0.07
Rated Heating Capacity (Btu/hr):	27000
Heating Input Power (kW):	0.06

Indoor Unit Type:	Round Flow Cassette
Rated Cooling Conditions	Indoor: 80°F DB/67°F WB
	Ambient: 95°F DB
Rated Heating Conditions	Indoor: 70°F DB
	Ambient: 47°F DB/43°F WB
Rated Piping Length (ft)	25
Rated Height Separation (ft)	0

**Indoor Unit Details**

Power Supply (V/Hz/Ph):	208-230/60/1ph
Power Supply Connections:	L1, L2, Ground
Min. Circuit Amps MCA (A):	0.5
Max. Overcurrent Protection (MOP) (A):	15
Dimensions (HxWxD):	9-11/16x33-1/16x33-1/16
Panel (HxWxD):	2x37-3/8x37-3/8
Net Weight (lbs):	48.5
Net Weight with Panel (lbs):	60.7

Airflow Rate (CFM wet coil)	780/620/470
Moisture Removal (pt/h):	
Gas Pipe Connection (inch):	5/8
Liquid Pipe Connection (inch):	3/8
Condensate Connection (inch):	1-1/4
Sound Pressure Level (dBA):	36
Sound Power Level (dBA):	
External Static Pressure/Max (inWg):	0 / 0
Controller Name:	

**FXFQ24PVJU**



**FXFQ24PVJU**

Std U.S. Warranty: 7yrs Compressor, 1yrs Parts

