

Project Name: _____
 Location: _____
 Engineer: _____
 Submitted to: _____
 Submitted by: _____
 Reference: _____

Approval: _____
 Date: _____
 Construction: _____
 Unit #: _____
 Drawing #: _____

Performance

Indoor Unit Model No: FXMQ48PVJU
Rated Cooling Capacity (Btu/hr): 48000
Sensible Capacity (Btu/hr): 35826
Cooling Input Power (kW): 0.46
Rated Heating Capacity (Btu/hr): 54000
Heating Input Power (kW): 0.449

Indoor Unit Type: Duct Mounted Standard Static (DC)
Rated Cooling Conditions Indoor: 80°F DB/67°F WB
 Ambient: 95°F DB/75°F WB
Rated Heating Conditions Indoor: 70°F DB/60°F WB
 Ambient: 47°F DB/43°F WB
Rated Piping Length (ft) 25
Rated Height Separation (ft) 0

Indoor Unit Details

Power Supply (V/Hz/Ph): 208-230/60/1ph
Power Supply Connections: L1, L2, Ground
Min. Circuit Amps MCA (A): 3.4
Max. Overcurrent Protection (MOP) (A): 15
Dimensions (HxWxD): 11-13/16x55-1/8x27-9/16
Panel (HxWxD): N/A
Net Weight (lbs): 101
Net Weight with Panel (lbs): _____

Airflow Rate (CFM wet coil) 1377//989
Moisture Removal (pt/h): _____
Gas Pipe Connection (inch): 5/8
Liquid Pipe Connection (inch): 3/8
Condensate Connection (inch): 1-1/4
Sound Pressure Level (dBA): 44
Sound Power Level (dBA): _____
External Static Pressure/Max (inWg): 0.8 / 0.8
Controller Name: _____

FXMQ48PVJU



FXMQ48PVJU

Std U.S. Warranty: 7yrs Compressor, 1yrs Parts

Project Name: _____
 Location: _____
 Engineer: _____
 Submitted to: _____
 Submitted by: _____
 Reference: _____

Approval: _____
 Date: _____
 Construction: _____
 Unit #: _____
 Drawing #: _____

Dimensional Drawing - Indoor Unit

FXMQ48PVJU

