

Submittal Data Sheet

Project Name:	
Location:	
Engineer:	
Submitted to:	
Submitted by:	
Reference:	

Approval:
Date:
Construction:
Jnit #:
Drawing #:

Performance

Outdoor Unit Model No:	RXYQ312PBYD
Туре:	Non-Ducted / Ducted
Rated Cooling Capacity (Btu/hr):	297000
Nom Cooling Capacity (Btu/hr):	312000
Cooling Input Power (kW):	25.83
SEER:	N/A
IEER:	18.2/17.0
Rated Heating Capacity (Btu/hr):	334000
Nom Heating Capacity (Btu/hr):	351000
Heating Input Power (kW):	29.66
Heating COP (Btu/hr / Btu/hr):	3.3/3.3
HSPF:	N/A
Heating COP 17F (Btu/hr / Btu/hr):	2.35/2.35

Condensing Unit Type:	26-Ton VRV-III Heat Pump
Unit Combination:	RXYQ120PBYD RXYQ120PBYD RXYQ72PBYD
Rated Cooling	Indoor: 80°F DB/67°F WB
Conditions	Outdoor: 95°F DB/75°F WB
Detect Llecting	Indoor: 70°F DB/60°F WB
Rated Heating Conditions	Outdoor: 47°F DB/43°F WB
Rated Piping Length (ft)	100 / 50
Rated Height Difference	<i>(ft)</i> 0

Condensing Unit Details

Power Supply (V/Hz/Ph):	460/60/3ph
Power Supply Connections:	L1, L2, L3 Ground
Min. Circuit Amps MCA (A):	21+21+16
Max. Overcurrent Protection (MOP)(A):	25+25+20
Max. Starting Current MSC(A):	81
Rated Load Amps RLA (A):	(5.4+8.4) x 2+7.1
Dimensions Height (Inch):	66-1/8
Dimensions Width (Inch):	134-3/8
Dimensions Depth (Inch):	30-1/8
Net Weight (lbs):	633+633+433

Compressor Type:	Inverter
Capacity Control Range (%):	5 - 100
Capacity Index Limit:	156 - 405.6 (130%)
Airflow Rate (CFM):	8,230+8,230+6,350
Gas Pipe Connection (inch):	1-3/8
Liquid Pipe Connection (inch):	3/4
H/L Pressure Connection (inch):	
H/L Equalizing Connection (inch):	
Sound Pressure Level (dBA):	64
Sound Power Level (dBA):	
Max. No. of Indoor Units:	54

System Details

Refrigerant Type:	R-410A
Holding Refrigerant Charge (lbs):	22.1+22.1+16.5
Additional Charge (lbs/ft):	install data
Pre-charge Piping (Length ft):	-
Max. Pipe Length (Total ft):	
Max. Pipe Length (Vertical ft):	164 ft (295 ft) / 295 ft
Max Height Seperation (Ind to Ind ft,):

Cooling Operation Range (°F):	23 - 110
Cooling Range w/Baffle (°F):	
Heating Operation Range (°F):	0 - 77 / (-4) - 60
Heating Range w/Baffle (°F):	

Daikin AC TRL Generated Submittal Data

Page 1 of 3 www.daikinac.com




Submittal Data Sheet

Project Name:	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:

Dimensional Drawing - Condensing Unit

RXYQ312PBYD





Submittal Data Sheet

Project Name:	
Location:	Approval:
Engineer:	Date:
Submitted to:	Construction:
Submitted by:	Unit #:
Reference:	Drawing #:



Daikin AC TRL Generated Submittal Data

RXYQ312PBYD

Std U.S. Warranty: 7yrs Compressor, 1yrs Parts

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)